

Royale Moisture Barrier

PE foam underlay designed for wood and laminate, suitable for domestic and contract installations.



Moisture Barrier	3mm
Construction	PE Foam
Nominal Thickness	3mm
Noise Reduction	22 dB ΔLW
Area Coverage	15m ²
Roll Dimensions	1m x 15m
Roll Weight	≈ 1.3kg

Technical Specifications		
Tested to EN	Result	Method
Thermal Resistance	1.39 TOG	EN BS 4745
R-Value	0.139m ² K/W	
U Value	7.194W/m ² K	
Temperature Limitation (Co)	-40 / +70	
Water Absorption (mg/m ²)	0.2...0.5	EN 12086:1997
Vapor Barrier Sd-Value (m)	>150	EN 12086:1997
Dynamic Load Resistance	<10000	EN 13793
Flammability Classification	Efi	EN 13501 - 1:2020
Reduction of Transmitted Impact Noise (dB)	22 dB ΔLW	EN 140-8, EN 717-2
Walking sound improvement	4%	IHD-W431

Product Specifications	
RH Levels	Supports up to 90% RH (relative humidity) levels
DPM Benefits	Helps prevent spillages on top of the carpet going through the subfloor as well as helping to protect the carpet in the event of dampness occurrence
Guarantee	Use Barrier Pro X Tape to join the seams

MANUFACTURER:

Distributed by Royale Flooring. From Wilsons Underlays Ltd. Dewsbury, WF13 3RD.

DISCLAIMER:

The data on this sheet is meant for information purposes only. The typical properties listed are the result of extensive research or laboratory testing, the materials used may vary and we cannot guarantee these results are obtained in practice. Users should conduct their own tests to determine the suitability of each material to its intended application.

ADDITIONAL INFORMATION:

Made of PE foam that is produced/expanded without CFC/HCFC. The usage of this product is not harmful to the environment and PE foam is 100% recyclable and also Freon free.

Royale™ is a trademark and division of Wilsons Underlays - for full Terms and Conditions visit wilsons-underlays.co.uk/terms-conditions

01924 451 138 | sales@wilsons-group.com

 wilsons-underlays.co.uk

